


Model TDC05180A20E

Features

Low VSWR
High Directivity
Broadband & Miniature Size

Technical Data Sheet			
Frequency Range	0.5~18GHz	Finish	Painted Blue_ RAL #5007
Insertion Loss	≤1.2dB (Excl. Coupling Loss 0.04dB)	Connector Body	Passivated Stainless Steel
Coupling Factor	≤20±1.0dB	Housing	Aluminum, 6061 T6 Clear Chem Conversion Film
Coupling Sensitivity	≤±1.0dB	Connector Pin	Beryllium Copper, Gold Plate
Directivity	≥10dB	Solder	Lead Free, RoHS Compliant
VSWR	Primary ≤1.50:1 Secondary ≤1.50:1	Operating Temperature	-55~+85°C
¹ Power Handling	Incident ≤30Watt; Reflected ≤30Watt	Operating Humidity	Up to 95%, Non- Condensing
Impedance	50Ω	Weight	65g
Port Connectors	SMA-Female		

¹Power Handling guaranteed when load's VSWR within 1.50:1.




Typical Performance


1. Coupling Factor & Sensitivity, Isolation, VSWR




Trc1 Mem5[Trc1] **S11** SWR 100 mU/ Ref 1 U Cal Invisib




Trc2 Mem6[Trc2] **S21** dB Mag 5 dB / Ref -30 dB



Trc3 Mem7[Trc3] **S21** dB Mag 0.5 dB / Ref -20.3 dB



Trc4 Mem8[Trc4] **S22** SWR 100 mU/ Ref 1 U Ca




3/2/2021, 4:58 PM




Typical Performance

2. Coupling Factor & Sensitivity, Isolation, VSWR



3/2/2021, 4:58 PM

3. Insertion Loss



3/2/2021, 4:59 PM

