


Model THC60265A

Features

Excellent phase & amplitude balance
Low Insertion Loss & VSWR
High Isolation


Technical Data Sheet			
Frequency Range	6~26.5GHz	Finish	Painted Blue_ RAL #5007
Nominal Split	3.01dB	Connector Body	Passivated Stainless Steel
Insertion Loss	≤1.6dB	Housing	Aluminum, 6061 T6
Isolation	≥16dB		Clear Chem Conversion Film
Amplitude Balance	≤±0.8dB	Connector Pin	Beryllium Copper, Gold Plate
Phase Balance	≤±8°	Solder	Lead Free, RoHS Compliant
VSWR	≤1.50:1	Operating Temperature	-55~+85°C
¹ Power Handling	Average ≤20Watt Peak ≤1KW	Operating Humidity	Up to 95%, Non-Condensing
Impedance	50Ω	Weight	30g
Port Connectors	2.92mm-Female		

¹Power Handling guaranteed when load's VSWR within 1.50:1.



Typical Performance

1. Insertion Loss, Amplitude & Phase Balance, VSWR




2/27/2023, 10:44 AM




Typical Performance

2. Insertion Loss, Amplitude & Phase Balance, VSWR



2/27/2023, 10:44 AM

2. Isolation



2/27/2023, 10:45 AM

