


## Model TDC04265A10

### Features

Low VSWR  
High Directivity  
Broadband & Miniature Size





Technical Data Sheet			
Frequency Range	0.4~26.5GHz	Finish	Painted Blue_ RAL #5007
Insertion Loss	≤1.7dB (Excl. Coupling Loss 0.46dB)	Connector Body	Passivated Stainless Steel
Coupling Factor	≤10±1.0dB	Housing	Aluminum, 6061 T6 Clear Chem Conversion Film
Coupling Sensitivity	≤±1.6dB@0.4-0.5GHz ≤±1.2dB@0.5-26.5GHz	Connector Pin	Beryllium Copper, Gold Plate
Directivity	≥10dB	Solder	Lead Free, RoHS Compliant
VSWR	Primary ≤1.50:1 Secondary ≤1.50:1	Operating Temperature	-55~+85°C
<sup>1</sup> Power Handling	Incident ≤20Watt; Reflected ≤1Watt	Operating Humidity	Up to 95%, Non- Condensing
Impedance	50Ω	Weight	70g
Port Connectors	2.92mm-Female		

<sup>1</sup>Power Handling guaranteed when load's VSWR within 1.50:1.



## Typical Performance

### 1. Coupling Factor & Sensitivity, Isolation, VSWR




1/4/2024, 4:41 PM




## Typical Performance

### 2. Coupling Factor & Sensitivity, Isolation, VSWR



1/4/2024, 4:41 PM

### 3. Insertion Loss



1/4/2024, 4:42 PM

