

Model THC06124B

Features

Excellent phase& amplitude balance


Low Insertion Loss& VSWR

High Isolation

Technical Data Sheet


Frequency Range	0.6~12.4GHz	Finish	Painted Blue_ RAL #5007
Nominal Split	3.01dB	Connector Body	Passivated Stainless Steel
Insertion Loss	≤8.0dB	Housing	Aluminum, 6061 T6 Clear Chem Conversion Film
Isolation	≥16dB		
Amplitude Balance	≤±1.3dB	Connector Pin	Beryllium Copper, Gold Plate
Phase Balance	≤±15°	Solder	Lead Free, RoHS Compliant
VSWR	≤1.80:1	Operating Temperature	-55~+85℃
¹ Power Handling	Average ≤20Watt Peak ≤1KW	Operating Humidity	Up to 95%,Non- Condensing
Impedance	50Ω	Weight	650g
Port Connectors	SMA-Female		

¹Power Handling guaranteed when load's VSWR within 1.50:1.



Typical Performance


1. Insertion Loss, Amplitude & Phase Balance, VSWR _ 0°



12/17/2024, 1:30 PM




2. Insertion Loss, Amplitude & Phase Balance, VSWR _ 180°



12/17/2024, 1:29 PM

3. Isolation



12/17/2024, 1:27 PM

