

Model THC0780B

Features

Excellent phase& amplitude balance


Low Insertion Loss& VSWR

High Isolation

Technical Data Sheet


Frequency Range	0.7~8GHz	Finish	Painted Blue_ RAL #5007
Nominal Split	3.01dB	Connector Body	Passivated Stainless Steel
Insertion Loss	≤2.5dB	Housing	Aluminum, 6061 T6 Clear Chem Conversion Film
Isolation	≥15dB		
Amplitude Balance	≤±1.0dB	Connector Pin	Beryllium Copper, Gold Plate
Phase Balance	≤±18°	Solder	Lead Free, RoHS Compliant
VSWR	≤1.60:1	Operating Temperature	-55~+85℃
¹ Power Handling	Average ≤50Watt Peak ≤1KW	Operating Humidity	Up to 95%,Non- Condensing
Impedance	50Ω	Weight	260g
Port Connectors	SMA-Female		

¹Power Handling guaranteed when load's VSWR within 1.50:1.



Typical Performance


1. Insertion Loss, Amplitude & Phase Balance, VSWR _ 0°



8/4/2020, 11:03 AM




2. Insertion Loss, Amplitude & Phase Balance, VSWR _ 180°



8/4/2020, 11:04 AM

3. Isolation



8/4/2020, 11:05 AM

