

Model THC1422B

Features

Excellent phase& amplitude balance


Low Insertion Loss& VSWR

High Isolation

Technical Data Sheet


Frequency Range	1.4~2.2GHz	Finish	Painted Blue_ RAL #5007
Nominal Split	3.01dB	Connector Body	Passivated Stainless Steel
Insertion Loss	≤0.5dB	Housing	Aluminum, 6061 T6 Clear Chem Conversion Film
Isolation	≥18dB		
Amplitude Balance	≤±0.5dB	Connector Pin	Beryllium Copper, Gold Plate
Phase Balance	≤±6°	Solder	Lead Free, RoHS Compliant
VSWR	≤1.30:1	Operating Temperature	-55~+85℃
¹ Power Handling	Average ≤30Watt Peak ≤1KW	Operating Humidity	Up to 95%,Non- Condensing
Impedance	50Ω	Weight	30g
Port Connectors	SMA-Female		

¹Power Handling guaranteed when load's VSWR within 1.50:1.



Typical Performance

1. Insertion Loss, Amplitude & Phase Balance, VSWR $_0^\circ$




11/9/2022, 2:55 PM




Typical Performance

2. Insertion Loss, Amplitude & Phase Balance, VSWR _ 180°



11/9/2022, 2:56 PM

3. Isolation



11/9/2022, 3:13 PM

