

Model THC2040B1

Features


Excellent phase& amplitude balance

Low Insertion Loss& VSWR

High Isolation


Technical Data Sheet			
Frequency Range	2~4GHz	Finish	Painted Blue_ RAL #5007
Nominal Split	3.01dB	Connector Body	Passivated Stainless Steel
Insertion Loss	≤0.5dB	Housing	Aluminum, 6061 T6 Clear Chem Conversion Film
Isolation	≥22dB		
Amplitude Balance	≤±0.5dB	Connector Pin	Beryllium Copper, Gold Plate
Phase Balance	≤±5°	Solder	Lead Free, RoHS Compliant
VSWR	≤1.25:1	Operating Temperature	-55~+85℃
¹ Power Handling	Average ≤50Watt Peak ≤1KW	Operating Humidity	Up to 95%,Non- Condensing
Impedance	50Ω	Weight	50g
Port Connectors	SMA-Female		

¹Power Handling guaranteed when load's VSWR within 1.50:1.



Typical Performance


1. Insertion Loss, Amplitude & Phase Balance, VSWR & $\pm 0^\circ$



11/14/2022, 4:36 PM




2. Insertion Loss, Amplitude/ Phase Balance, VSWR _ 180°



11/14/2022, 4:35 PM

3. Isolation



11/14/2022, 4:38 PM

